

When it is about **knowledge** and **experience** Roton Lifts Europe is the right address to turn to. We will make sure to give you the right attention and advice. In many cases the **quality** and **safety** of your lift is the first priority.

Because we cooperate with the most important manufacturers in Europe we can offer you different possibilities with different prices to compare.

An unique selling point is that **we can deliver fast**, this is because we cooperate with manufacturers who do have enough manpower in the factory to build your lift.

Of course we provide all **drawings** you need (also DWG), together with complete **installation**.

When desired we take care of the **maintenance** and possible malfunction of your lift.





## Our scissortables are equipped standard with:

- Controls with 3 meters curly cable hold to run up/down-emergency stop.
- Hydraulic unit with met pump, oiltank, highpressure and lowering valve.
- Steering 24 Volt DC, advanced steering is possible.
- A safety bar all around underneath the platform.
- Protectionclass IP54.
- An endswitch for upper landing (also possible for in between landing and lower landing).
- Mechanical legs for maintenance (work under the lift).
- All components mechanical and electrical are made from the highest quality.
- Safety valve in cilinder in case of lost oilpressure in hydr. hose.

- ✓ Fast delivery
- ✓ Flexibility
- Delivery with CE certificate
- ✓ Available in any RAL color
- ✓ Factory warranty of 1 year

| Articlenumber | Туре       | Load<br>(kg) | Lowest height (mm) | Stroke<br>(mm) | Total height<br>(mm) | Platformsize<br>LxW (mm) | Power<br>(kW) | Weight (kg) | Speed<br>(sec) |
|---------------|------------|--------------|--------------------|----------------|----------------------|--------------------------|---------------|-------------|----------------|
| U-shape       |            |              |                    |                |                      |                          |               |             |                |
| 600-0087      | RO-600-1U  | 600          | 80                 | 670            | 750                  | 1350 x 1150              | 0,4           | 210         | 15 sec         |
| 900-0088      | RO-900-1U  | 900          | 80                 | 670            | 750                  | 1350 x 1150              | 0,4           | 220         | 16 sec         |
| 1200-0089     | RO-1200-1U | 1200         | 80                 | 670            | 750                  | 1350 x 1150              | 0,4           | 220         | 17 sec         |
| 1500-0090     | RO-1500-1U | 1500         | 80                 | 670            | 750                  | 1350 x 1150              | 0,4           | 240         | 19 sec         |
| Low built     |            |              |                    |                |                      |                          |               |             |                |
| 600-0091      | RO-600-1L  | 600          | 80                 | 670            | 750                  | 1400 x 900               | 0,4           | 210         | 15 sec         |
| 600-0092      | RO-600-1L  | 600          | 80                 | 900            | 980                  | 1500 x 1000              | 0,8           | 260         | 17 sec         |
| 900-0093      | RO-900-1L  | 900          | 80                 | 670            | 750                  | 1400 x 900               | 0,4           | 220         | 16 sec         |
| 900-0094      | RO-900-1L  | 900          | 80                 | 900            | 980                  | 1500 x 1000              | 0,8           | 280         | 19 sec         |
| 1200-0095     | RO-1200-1L | 1200         | 80                 | 670            | 750                  | 1400 x 900               | 0,4           | 240         | 18 sec         |
| 1200-0096     | RO-1200-1L | 1200         | 100                | 900            | 1000                 | 1500 x 1000              | 1,2           | 300         | 19 sec         |
| 1500-0097     | RO-1500-1L | 1500         | 80                 | 670            | 750                  | 1400 x 900               | 0,4           | 260         | 21 sec         |
| 1500-0098     | RO-1500-1L | 1500         | 100                | 900            | 1000                 | 1500 x 1000              | 1,2           | 320         | 21 sec         |